

Bilge Pumps

Submersible Bilge and Thru-Hull Pumps

Letter	Item #	Description	Outlet
A1	69300	600 GPH	3/4"
A2	69301	800/1100 GPH	3/4" & 1 1/8"
A3	69330	Float Switch (20 Amp)	-
A4	69310	AUTOMATIC 600	3/4"
A5	69311	AUTOMATIC 800/1100 GPH	3/4" & 1 1/8"
A6	69320	Thru-Hull Pump, 600 GPH	3/4" & 1 1/8"
A7	69321	Thru-Hull Pump, 800/1100 GPH	3/4" & 1 1/8"



A. Bilge Pumps Self-priming, 12V centrifugal pumps. Ideal for all watercraft. Designed for easy installation and retrofitting. 800 GPH 3/4" outlet and 1100 GPH 1 1/8" outlets in one package. Cartridge style pump head. Pump body accepts both 3/4" and 1 1/8" screw-on outlets creating 2 pumps in 1. Universal strainer base is connection-compatible: fits Attwood Tsunami, Rule, Johnson/Mayfair cartridge pumps. Screw mounting holes match Rule and Attwood Tsunami. Meets ABYC, Coast Guard and ISO marine standards. Ignition protection. Low power draw. Runs dry without damage. US Patent D689,908. 1 Year Warranty.

B. Portable Aerator Self-priming, centrifugal pump. Ideal for coolers, buckets & baitwells. Powered by 3 D-cell batteries (not included). Powerful spray aerates water to keep bait alive. Increased oxygen level keeps bait lively. Adjustable spray head to increase or decrease spray. Wide strainer base adds stability. Suction cup or screw mount. Submersible. Runs dry without damage. US Patent D689,907.

69340 Portable Aerator

C. Portable Pump Self-priming, centrifugal pump. Ideal for jon boats, utility boats, dinghies, inflatable boats and all other small watercraft. Also great for removing fluids from many non-marine applications. Powered by 3 D-cell batteries (not included). 250 GPH flow rate at zero head. 3/4" x 36" hose wraps around body for stowage. Wide strainer base adds stability. Suction cup or screw mount. Includes clip to attach hose to transom. Submersible. Runs dry without damage. Dimensions: 5" x 5" x 12". US Patent D689,907.

69341 Portable Pump

A. Macerator Pump Designed specifically for sanitation waste and fish box evacuations, this high-powered pump incorporates a high quality motor with seamless motor tube and o-ring sealed motor end frames. High-speed rotary cutter shreds waste efficiently, producing a higher discharge capacity. Design allows for direct replacement with other macerators for easy installation. 13 GPM (49.2 LPM). Self-priming to 5'. O-ring sealed motor end frames. Heavy duty armature shaft seal. Manual turn key with rear O-ring seal. Innovative internal housing design. Seamless motor tube. Dual blade design. Premium impeller. Ignition protection. 1.5" intake hose. 12V DC.

69390 Macerator Pump



B. Super-Duty Washdown Pump Self-priming, 12V diaphragm pumps with sealed, pressure switch control and vibration dampening polymer isolating mounting base. Washdown pumps are ideal for cleaning leisure boats, fish boxes, anchor chains and dinghies. Suitable for fresh and salt water. All models include filter and fittings. 70 PSI. 5.3 gallons/minute flow rate. 6 amps. Smooth operation and flow. Quiet running. Runs dry without damage. Seamless motor shell. Low power draw. Ignition protected. Easy quick-connect fittings. 1 year warranty.

69381 Super-Duty Washdown Pump



C. Portable Washdown Pump Kit This easy-to-use washing kit is built with a high pressure diaphragm pump that is self-priming, can run dry without damage and won't overheat. Just connect to a garden hose or use the supplied input hose to draw water directly from the lake, ocean or even a bucket and you are ready to wash. Includes: Fully sealed pump, adjustable spray nozzle, 6.6 ft. (2 m) input water hose with quick-connect fitting and filter, 12.3 ft (3.75 m) spray hose with quick-connect fittings and 2 cord options for 12V power – battery clips for direct battery connection and a DC power port adaptor. Carrier size: 13.8" L x 11.3" W x 12.5" H. 2 gallons/minute flow rate. Suction capacity 6 ft. 100 PSI. 14 amps.

69380 Portable Washdown Pump Kit

